

MODEL	MATERIAL	CONNECTION	ELECTRICAL CONTACTS	ELECTRICAL CHARACTERISTICS					TEMPERATURE		MAX. PRESSURE
				POWER COMMUTABLE IN D.C.	POWER COMMUTABLE IN A.C.	INTENSITA' DI CORRENTE IN C.A.	CURRENT STRENGHT	PROTECTION	PVC CABLE	SILICONE CABLE	
IEG - 1	BRASS	1/8" GAS MALE	SPST	40 W	40 V.A.	2 A	220 VDC 220VAC	IP 65	-20 +80 °C	-20 +120 °C	5
IEG - 1P	NYLON								-20 +80 °C		
IEG - 2	BRASS		SPDT	20 W	20 V.A.	1 A	150 VDC 150VAC		-20 +80 °C	-20 +120 °C	
IEG - 2P	NYLON								-20 +80 °C		
IEG - S1M	BRASS	1/8" GAS MALE	SPST	80 W	80 V.A.	1,3 A	250 VDC 250VAC	IP 65	-20 +80 °C	-20 +120 °C	10
IEG - S1F		1/8" GAS FEMALE									
IEG - S2M		1/8" GAS MALE	SPDT	30 W		0,5 A	220 VDC				
IEG - S2F		1/8" GAS FEMALE									